



Norme / Standards:	CEI EN 60076 - CEI EN 50588-1
Classe Isolamento (Aumento Temp. Olio - Awo.) / Insulating Class (Temp. Rise Oil - Winding):	A (60/65 K)
Classe Isolamento MV (Classe 36) / Insulation Class MV (Class 36):	36 kV FI 70 kV BIL 170 kV
Classe Isolamento MV (British Design Class 12) / Insulation Class MV (British Design Class 12):	7,2 kV FI 20 kV BIL 60 kV - 12 kV FI 28 kV BIL 75 kV
Classe Isolamento LV / Insulation Class LV:	1,1 kV FI 3 kV
Frequenza / Frequency:	50 Hz
Regolazione MV / Tappings MV:	± 4% or ± 2 x 2,5%
Tolleranza / Tolerance:	Tolleranza zero sulle perdite / No tolerance on the losses

CLASS 36 kV

Power kVA	P <sub>0</sub> W	P <sub>cc</sub> (75 °) W	U <sub>k</sub> (75 °) %	LwA dB(A)	Total Weight Kg	Oil Weight Kg	A mm	B mm	C mm	D mm	M mm	P mm	J mm	G mm
50	A <sub>0</sub> 103	C <sub>k</sub> 1210	4	39	720	160	950	740	1390	910	125	520	380	90
100	A <sub>0</sub> 166	C <sub>k</sub> 1925	4	41	810	180	980	750	1440	960	125	520	380	90
160	A <sub>0</sub> 241	C <sub>k</sub> 2585	4	44	1010	230	1020	790	1520	1040	125	520	380	90
200	A <sub>0</sub> 287	C <sub>k</sub> 3025	4	44	1130	250	1050	840	1520	1040	125	520	380	100
250	A <sub>0</sub> 345	C <sub>k</sub> 3575	4	47	1260	280	1050	910	1620	1140	125	520	380	100
315	A <sub>0</sub> 414	C <sub>k</sub> 4290	4	49	1370	300	1120	880	1660	1180	125	670	380	100
400	A <sub>0</sub> 494	C <sub>k</sub> 5060	4	50	1620	340	1140	900	1780	1300	125	670	380	100
500	A <sub>0</sub> 586	C <sub>k</sub> 6050	4	51	1850	380	1140	970	1780	1300	125	670	380	100
630	A <sub>0</sub> 690	C <sub>k</sub> 7150	4	52	2210	440	1210	1050	1900	1420	125	670	380	100
630	A <sub>0</sub> 690	C <sub>k</sub> 7150	6	52	2120	460	1260	980	1860	1380	125	670	380	100
800	A <sub>0</sub> 747	C <sub>k</sub> 9240	6	53	2430	510	1600	990	1900	1420	125	670	380	100
1000	A <sub>0</sub> 885	C <sub>k</sub> 11550	6	55	2950	590	1690	1090	2100	1620	160	820	380	100
1250	A <sub>0</sub> 1092	B <sub>k</sub> 12100	6	56	3390	660	1720	1090	2100	1620	160	820	380	100
1600	A <sub>0</sub> 1380	B <sub>k</sub> 15400	6	58	3900	730	1870	1180	2140	1660	160	820	380	180
2000	A <sub>0</sub> 1667	B <sub>k</sub> 19800	6	58	4560	920	1940	1220	2180	1700	200	820	380	180
2500	A <sub>0</sub> 2012	B <sub>k</sub> 24200	6	60	5320	1000	2030	1350	2280	1800	200	820	380	220
3150	A <sub>0</sub> 2530	B <sub>k</sub> 30250	6	63	7140	1570	2530	1340	2470	1990	200	1070	380	220